

AEON-LT

AEON HEVC Transmitter Lite

Overview:

A compact COFDM digital video transmitter, specifically designed for high quality wireless link applications. With proven Domo COFDM and next generation HEVC encoder technology at its core enabling Ultra High Definition images, the small size and actively cooled enclosure give maximum operational performance.

Designed to offer future proof connectivity, the unit supports quad 3G-SDI video inputs. Two true balanced audio inputs are included with phantom power. The transmitter has an integrated control panel with sunlight-readable display covering all major functions and has sixteen user-defined presets, as well as IP based control.

The HEVC codec used in AEON products offers a step change in compression efficiency over H.264 systems, whilst maintaining low end to end latency suitable for live events.



Features and Benefits:

Ultra-low latency HEVC SD, HD and 4K encoding

Video formats up to 2160p60, 10-bit and 4:2:2 chroma sampling, future HDR support

Industry standard DVB-T modulation for interoperability with existing systems

Domo Broadcast UMVL modulation for enhanced high frequency/high speed performance

Controlled via IP or integrated sunlight-readable display

Available as V-mount, AB-mount or no battery mount options

Designed for sports & events coverage, newsgathering and wireless studio camera applications

Low power consumption and active cooling for extended field performance

Product Information:

Product Includes

CA0579	XLR audio input cable
CA3348 x 4	SDI HD-BNC to BNC cable, 0.25m
SA4329	AEON Lite USB support stick

Accessory Options (sold separately)

CA0340	RS232 data cable
CA0579	Additional second channel XLR audio input cable
CA3421	OB Lemo 15V 6.0A 90W desktop PSU
PRORXD-8-2RU-AEON	4K Professional HEVC Receiver and Decoder

Related Documents

100273	AEON Lite HEVC Transmitter User Guide
--------	---------------------------------------

AEON-LT

AEON HEVC Transmitter Lite

Technical Specification

IO

SD/HD 3G-SDI inputs	HD-BNC x 4
**Serial data input	4-way 0B Lemo
Power input	4-way 0B Lemo
RF COFDM transmitter	N-type
Balanced audio input	5-way 0B Lemo x 2
Battery mount	V-Lock or Anton Bauer plates
Ethernet	RJ45

DVB-T Modulation

DVB-T bandwidth	8MHz, 7MHz and 6MHz modes
DVB-T dual pedestal	2x8MHz, 2x7MHz and 2x6MHz modes
DVB-T FEC	1/2, 2/3, 3/4, 5/6, 7/8
DVB-T constellation	QPSK, 16QAM, 64QAM
DVB-T guard interval	1/4, 1/8, 1/16, 1/32
DVB-T bitrates	3.732Mbps to 31.668Mbps

UMVL Modulation

UMVL bandwidth	8MHz, 7MHz and 6MHz modes
UMVL FEC	1/3, 2/3
UMVL constellation	QPSK, 16QAM, BPSK, 8PSK
UMVL guard interval	1/8, 1/16
UMVL bitrates	1.317kbps to 14.869Mbps

Video

SD input format	SMPTE-259M 720x576i 50Hz 720x480i 59Hz
HD input format	SMPTE-292M/424M 1920x1080i 60/59.94/50Hz 1920x1080p 60/59.94/50/30/29.97/25/24/ 23.97Hz *1920x1080psf 30/29.97/25/24/23.97Hz 1280x720p 60/59.94/50Hz
Ultra HD input format	SMPTE ST-2081/2082 3840x2160p 60/59.94/50/30/29.94/25/24/ 23.97Hz
HEVC compression	HEVC/H.265/MPEG-H Part 2 8-bit or 10-bit, 4:2:0 or 4:2:2
H.264 compression	AVC/H.264/MPEG-4 Part 10
MPEG-2 compression	H.262/MPEG-2 Part 2

Audio

Analogue audio input	Two balanced analogue stereo pairs +4dBu max input level
Analogue phantom power	48V switchable
Digital audio input	SD/HD 3G-SDI de-embedding
Sample rate	48kHz
Coding modes	Up to 8 channels (4 pairs) LPCM

AEON-LT

AEON HEVC Transmitter Lite

Technical Specification (con't):

Other

RS232 data input	1k2 to 115k2, 7/8 bit, no/odd/even parity
Front panel	Built in display with button control

Power

DC input	9.2V to 17.8V reverse polarity protected
Power consumption	30W max

Physical

Dimensions (no battery mount)	177mm (L), 125mm (W), 50mm (D)
Weight	1080g

Environment

Temperature range	-10°C to +50°C
Humidity	Less than 85% non-condensing

Frequency

198270	1.98-2.70GHz
300370	3.00-3.70GHz
700750	7.00-7.50GHz

Software License Code

Silver (included)	DVB-T, Ultra Mobile Video Link (UMVL), Dual Pedestal, Single HD Encoder
LIC-AEON-PSF	PSF Video Formats

*Additional license feature

**Future development

Export of encrypted products is subject to United Kingdom regulatory export controls.

For further information contact your Sales Account Manager, one of our Regional Sales Offices, or email solent.enquiries@domotactical.com

DTC – Herndon (Headquarters)
2303 Dulles Station Boulevard
Suite 205
Herndon, VA
20171, USA

T: +1 800 665 4648

DTC – Tampa
3845 Gateway Centre Boulevard
Suite 360
Pinellas Park, FL
33782, USA

T: +1 727 471 6900

DTC – Solent
Fusion 2, 1100 Parkway
Solent Business Park
Whiteley, Hampshire
PO15 7AB, UK

T: +44 (0) 1489 566 750

DTC – Randers
Haraldsvej 64B
DK-8960
Randers SØ
Denmark

T: +45 8791 8100

DTC – Singapore
21 Media Circle
Infinite Studios #05-06
Singapore
138562

T: +65 6339 0508

DTC – Brazil
Alameda Araguaia 2
190 – Ed. CEA II – suite 1109
Alphaville - Barueri
São Paulo, Brazil
06455-000
T: +55 11 2321 5055

The information contained in this document is the property of Domo Tactical Communications (DTC) Ltd. This document and the information contained herein is provided for evaluation purposes only and is subject to change without notice. Domo Tactical Communications (DTC) Ltd assumes no responsibility for errors that might appear in this document and gives no representations or warranties as to the accuracy of the information contained herein, including but not limited to the suitability and performances of the product or its intended application. Any copying or reproduction in any form whatsoever is prohibited without the written permission of DTC.

© Copyright Domo Tactical Communications (DTC) Limited 2016. All Rights Reserved.

1118

domotactical.com



Planet Communications Asia PLC.

157 Soi Ramindra 34, Ramindra Rd., Tarang, Bangkok 10230

Tel: +66 2 792 2400 | Fax: +66 2 792 2499, +66 2 943 5771 | E-mail: sales@planetcomm.com



PlanetComm: