

SOL8SDR-R

SOL8 Software Defined Radio (Robust)

Overview:

The SOL8 Software Defined Radio is an ultra-miniature COFDM digital video transceiver from Domo Tactical Communications (DTC), designed specifically for Point of View (PoV), body worn and concealment applications. Dependent on the applications loaded the platform can operate as a Transmitter, Dual Encoder, Standard IP Mesh and MIMO IP Mesh. Further information on software capability can found in the SDRAPP datasheets.

Three enclosure variants are available: Concealment (-C), Robust (-R), Plain (-P). Robust (-R) provides a passively cooled IP66 rated enclosure ideal for outdoor, or body worn applications.

The UHF version is larger than the standard SOL8SDR-R due to the lower frequency of operation (320-470MHz). Please see the SOL8SDR UHF Operation Guidelines publication for important application notes.



Features and Benefits:

- 2x100mW COFDM transceivers for use as COFDM Transmitter or IP Mesh
- ISM band telemetry transceiver for control, PTZ and low power standby
- Dual SD/HD-SDI video inputs for recording, transmission and analysis
- Microphone inputs and headphone output for recording, transmission or talkback
- Growing USB support for peripherals such as 3G/4G/Wi-Fi dongles
- Ethernet, RS232 and RS485 connectivity and 128GB built in storage
- Robust packaging with IP66 rated connectors
- Very low power consumption: typically 7.5W
- Exceptionally small size: 130mm x 100mm x 25mm (30.5mm UHF)
- Weights only 314-372g

Product information:

Product Includes:

AP007377	Micro-B USB Cable
CA0002	12V DC Power lead Lemo-wire 3m
CA3173	UltiMate DC power Cable
CA3123	UltiMate Microphone/Headphone Cable
CA2521	UltiMate Ethernet Breakout
CA2522	UltiMate USB Breakout
CA2396	DIN 1.0/2.3 to BNC Female Cable x 2
SA3741	SOL8SDR-R Support USB stick

Accessory Options (sold separately):

SDRAPP-ENC	SDR Application IP Encoder
SDRAPP-MESH	SDR Application IP Mesh NETNode
SDRAPP-TX	SDR Application COFDM Transmitter
SOL8SDR-RSK	SOL8SDR Robust Surveillance Kit
CA2520	UltiMate DC/Audio/RS232 Cable
CA3164	UltiMate DC/USB/RS485 Wire Breakout
AES128TX	AES 128-bit Encryption License
AES256TX	AES 256-bit Encryption License

Related Documents:

100217	SOL8SDR Hardware and Basic Setup Guide
--------	--

SOL8SDR-R

SOL8 Software Defined Radio (Robust)

Technical specification

IO

RF COFDM Transceiver 1	SMA (female)
RF COFDM Transceiver 2	SMA (female)
RF Telemetry Transceiver	SMA (female)
Video SD/HD-SDI 1	DIN 1.0/2.3 (female)
Video SD/HD-SDI 2	DIN 1.0/2.3 (female)
USB Control and Download	Fischer UltiMate (to USB 2.0 Micro-B)
Power Input	Fischer UltiMate (to 4-way Lemo)
Power Output	Fischer UltiMate (to 4-way Lemo)
PA Control	Fischer UltiMate (to wire)
Microphone 10V	Fischer UltiMate (to wire)
Microphone/Line Input	Fischer UltiMate (to male RCAs)
Headphone Output	Fischer UltiMate (to 3.5mm socket)
PTZ Control, or Data IO	Fischer UltiMate (to 9-way D-Sub)
Gigabit Ethernet	Fischer UltiMate (to RJ45 Magnetics)

COFDM Transceivers

Power	100mW (+20dBm) per output, 200mW total
Power Step	0.25dB incremental control
Tuning Range	Frequency variant dependant
Tuning Step	125kHz
Required Application	SDRAPP-TX or SDRAPP-MESH

Telemetry Transceiver

Power	+11dBm frequency dependant
Tuning Range	Frequency variant dependant
Receiver Sensitivity	-114dBm
Required Application	SDRAPP-TX

Video

Digital Input	Dual SD/HD-SDI (supports SOL8SDI for HDMI or composite)
Required Application	SDRAPP-ENC

Audio

Headphone Output	Mono headphone driver
Analogue Input	High gain microphone stereo pair 10V microphone bias (cable dependant)
Digital Input	SD/HD-SDI de-embedding
Required Application	SDRAPP-ENC or SDRAPP-MESH

Data

Data Configuration	1k2 to 115k2, 7/8 bit, no/odd/even parity
Data Interface	RS232 (optional cable) or RS485 (optional cable) or USB peripherals

Storage

Medium	Internal microSD 128GB (>8 hours recording at max DVB-T bitrate) (>29 hours recording at max NB bitrate)
--------	--

Control

USB	PC Application control and SD card mounting
Ethernet	PC Application control and file download Web GUI control and file download
Access	User, Super User and Admin accounts

Physical

Dimensions	L 130mm, W 100mm, H 25mm L 130mm, W 100mm, H 30.5mm (UHF)
Weight	314g 372g (UHF)

Power

DC Input	8V to 18V reverse polarity protected
DC Output	1A pass-through (switchable)
Camera/Adapter Power	5V over video input (switchable)
Typical Power Consumption	7.5W (SD), 8.5W (HD), 9.5W (Dual)

Environment

Temperature Range	-20°C to +60°C
Humidity	Less than 85% Non-Condensing
Cooling	Passive, external heat sink or fan
Sealing	IP66
EMC Conformance	CE marked

SOL8SDR-R

SOL8 Software Defined Radio (Robust)

Technical specification (con't):

Frequency

040091	320-470MHz + 902.00-928.00MHz
132043	1.14-1.50GHz + 433.05-434.79MHz
201043	1.67-2.35GHz + 433.05-434.79MHz
201091	1.67-2.35GHz + 902.00-928.00MHz
234043	1.98-2.70GHz + 433.05-434.79MHz
234091	1.98-2.70GHz + 902.00-928.00MHz
470043	4.40-5.00GHz + 433.05-434.79MHz
470091	4.40-5.00GHz + 902.00-928.00MHz

Software License Code Includes

Silver (included)	None included SDRAPP required
Gold	N/A
Platinum	N/A

Export of encrypted products is subject to United Kingdom regulatory export controls.

For further information contact your Sales Account Manager, one of our Regional Sales Offices, or email solent.enquiries@domotactical.com

DTC – Solent
Fusion 2, 1100 Parkway
Solent Business Park
Whiteley, Hampshire
PO15 7AB, UK

T: +44 (0) 1489 566 750

DTC – Tampa (Head Office)
3845 Gateway Centre Boulevard
Suite 360
Pinellas Park, FL
33782, USA

T: +1 727 471 6900

DTC – Randers
Haraldsvej 64B
DK-8960
Randers SØ
Denmark

T: +45 8791 8100

DTC – Singapore
21 Media Circle
Infinite Studios #06-04
Singapore
138562

T: +65 6643 4700

DTC – Brazil
Alameda Araguaia 2
190 – Ed. CEA II – suite 1109
Alphaville - Barueri
São Paulo, Brazil
06455-000

T: +55 11 2321 5055

The information contained in this document is the property of Domo Tactical Communications (DTC) Ltd. This document and the information contained herein is provided for evaluation purposes only and is subject to change without notice. Domo Tactical Communications (DTC) Ltd assumes no responsibility for errors that might appear in this document and gives no representations or warranties as to the accuracy of the information contained herein, including but not limited to the suitability and performances of the product or its intended application.

© Copyright Domo Tactical Communications (DTC) Limited 2016. All Rights Reserved.

1216

domotactical.com



Planet Communications Asia PLC.

157 Soi Ramindra 34, Ramindra Rd., Tarang, Bangkhen, Bangkok 10230
Tel: +66 2 792 2400 | Fax: +66 2 792 2499, +66 2 943 5771 | E-mail: sales@planetcomm.com



PlanetComm: