4.5M C or Ku-Band Receive Only

Series 1451

Technical Specifications

Electrical	C-Band Linear	C-Band Circular	Ku-Band Linear
Antenna Size	4.5 M (15 ft.)	4.5 M (15 ft.)	4.5 M (15 ft.)
Operating Frequency (GHz)	3.625 - 4.2 GHz	3.625 - 4.2 GHz	10.95 - 12.75 GHz
Midband Gain (+/5dB)	42.9 dBi	42.6 dBi	51.9 dBi
3dB Beamwidth	1.2°	1.2°	0.41°
Feed Interface	CPR 229	CPR 229	WR 75
Cross-Pol Isolation	>30 dB Min. (on axis)	>17 dB Min. (on axis)	>30 dB Min. (on axis)
First Sidelobe (typical)	- 20 dB	- 20 dB	- 20 dB
VSWR	1.3:1 Max.	1.5:1 Max.	1.3:1 Max.

Mechanical	
Reflector Material	Glass Fiber Reinforced Polyester SMC
Antenna Optics	8 Piece Axisymmetric, Prime Focus
Mast Pipe Size	10" SCH 40 Pipe (10.75" OD) 27.30 cm.
Elevation Adjustment Range	5° to 90° Continuous Fine Adjustment
Azimuth Adjustment Range	360° Continuous
Shipping Specifications (Weight)	950 lbs. (428 kg.)

Environmental Performance	
Wind Loading Operational Survival	45 mph (72 km/h) 125 mph (201 km/h)
Temperature Operational	-40° to 140° F (-40° to 60° C)
Relative Humidity	0 to 100% (Condensing)
Rain (operational)	1/2' / Hr.
Atmospheric Conditions	Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas
Solar Radiation	360 BTU/h/ft2

GENERAL DYNAMICS

SATCOM Technologies

1500 Prodelin Drive • Newton, NC 28658 USA • Telephone: +1-828-464-4141 • Fax: +1-828-464-4147 Email: vsat@gdsatcom.com • Web Site: www.gdsatcom.com

© 2012 General Dynamics. All rights reserved. General Dynamics reserves the right to make changes in its products and specifications at anytime and without notice. All trademarks indicated as such herein are trademarks of General Dynamics. All other product and service names are the property of their respective owners. ® Reg. U.S. Pat. and Tm. Off.

1000-002 Rev 01/12.



